HALO PD22753-UNV-010

PENDANTS









PD22753-BK-UNV-010 PD22753-BS-UNV-010

Brushed Silver

PD22753-WH-UNV-010 White

SPECIFICATION DETAILS

Fixture Dimensions D52" x H4-1/4" Light Source LED with DC Driver Wattage 118W Total Lumens 10500lm Delivered Lumens BK-2433lm; BS -2826lm; WH-3356lm; Voltage 120-277V Color Temperature 3000K CRI (Ra) 90CRI Optional Color Temps 2700K - 5000K Available, Minimum Order of Apply LED Rated Life 50,000 hours Dimming 100% - 10%, TRIAC or ELV Dimmer (Not Included)	Quantities
Wattage 118W Total Lumens 10500lm Delivered Lumens BK-2433lm; BS -2826lm; WH-3356lm; Voltage 120-277V Color Temperature 3000K CRI (Ra) 90CRI Optional Color Temps 2700K - 5000K Available, Minimum Order of Apply LED Rated Life 50,000 hours Dimming 100% - 10%, TRIAC or ELV Dimmer (Not Inc.)	Quantities
Total Lumens 10500lm	Quantities
Delivered Lumens BK-2433Im; BS -2826Im; WH-3356Im; Voltage 120-277V Color Temperature 3000K CRI (Ra) 90CRI Optional Color Temps 2700K - 5000K Available, Minimum Order (Apply) LED Rated Life 50,000 hours Dimming 100% - 10%, TRIAC or ELV Dimmer (Not Inc.)	Quantities
Voltage 120-277V Color Temperature 3000K CRI (Ra) 90CRI Optional Color Temps 2700K - 5000K Available, Minimum Order of Apply LED Rated Life 50,000 hours Dimming 100% - 10%, TRIAC or ELV Dimmer (Not Inc.)	Quantities
Color Temperature 3000K CRI (Ra) 90CRI Optional Color Temps 2700K - 5000K Available, Minimum Order of Apply LED Rated Life 50,000 hours Dimming 100% - 10%, TRIAC or ELV Dimmer (Not Inc.)	Quantities
CRI (Ra) 90CRI Optional Color Temps 2700K - 5000K Available, Minimum Order of Apply LED Rated Life 50,000 hours Dimming 100% - 10%, TRIAC or ELV Dimmer (Not In-	Quantities
Optional Color Temps 2700K - 5000K Available, Minimum Order of Apply LED Rated Life 50,000 hours Dimming 100% - 10%, TRIAC or ELV Dimmer (Not In-	Quantities
Apply LED Rated Life 50,000 hours Dimming 100% - 10%, TRIAC or ELV Dimmer (Not In:	Quantities
Dimming 100% - 10%, TRIAC or ELV Dimmer (Not In-	
or 0-10V Dimmer (Not included)	cluded)
Diffuser Details White Acrylic Diffuser	
Adjustable Yes	
Wire Length 120" Max	
Wire Type Clear SSL Wire	
Minimum Hang Height 42"	
Sloped Ceiling Adaptable Yes	
Sloped Ceiling Adaptable Yes Location Dry	
Location Dry	
Location Dry Illumination Direction Up and Down	
Location Dry Illumination Direction Up and Down Canopy Dimensions D11-7/8" x H2"	

^{*} For custom options, consult factory for details.

KUZCO


CANADA: 19054 28TH AVENUE - SURREY, BC V3Z 6M3 USA: 3035 E. LONE MOUNTAIN ROAD - LAS VEGAS, NV 89081

WWW.KUZCOLIGHTING.COM © 2017 KUZCO LIGHTING. ALL RIGHTS RESERVED.


PROJECT

DESCRIPTION

The circular Halo light makes a sleek and bold statement. This fixture illuminates your room in a smooth circular pattern, which is both modern and minimal. Available in four sizes and three finishes: Black, White and Brushed Nickel. They can be arranged in a tier formation to complement your space.



Side Canopy Option Ø11-7/8"



COMMENT





^{*} For warranty information, please visit www.kuzcolighting.com/warranty